

Product Fiche

Supplier name	Arada
Product Code	SOL7-INSET-S4
Energy Efficiency Class (wood)	А
Direct Heat Output (wood)	7.1 Kw
Indirect Heat Output (wood)	N/A
Energy Efficiency Index (wood)	98.4
The useful energy efficiency at nominal heat output and at minimum load (wood)	75.4 %

Specific precautions that shall be taken when the local space heater is assembled, installed or maintained:

Product should be installed in accordance with local building regulations. Appliance will become very hot during use.

Dimensions

Width	517 mm
Height	580 mm
Depth	469 mm
Depth into fireplace	316 mm
Width into fireplace	394 mm
Height into fireplace	544 mm
Depth of front fascia	100 mm
Flue diameter	127 mm
Flue outlet angle from vertical	30°
Ideal log length / diameter	300mm / 100mm

Features

Inset
Yes
Yes
No
No
91 Kg
85 Kg

Performance - Wood & Solid Fuel

	Wood Fuel	Solid Fuel
Energy Efficiency Class	А	E
Nett Efficiency	75.4 %	75.8 %
Nominal Output	7.1 kW	7.1 kW
Mean Co Emission (@13% O2)	0.11 %	0.08 %
DIN+ particulate	27 Nmg/m ³	27 Nmg/m ³
Mean NOx Emission (@13% O2)	95 Nmg/m ³	159 Nmg/m ³
Mean OGC Emission (@13% O2)	92 Nmg/m ³	43 Nmg/m ³
Flue Gas Mass Flow	6.23 g/s	6.4 g/s
Flue Gas Temperature	326 °C	332°C
Typical Fuel load for nominal rated output per hour (kWh/Kg)	1.62(Seasoned hardwood)	1.08 (MSF Maxibrite)

Minimum distance to combustibles

Single Walled Flue	
Above	200 mm
Side	175 mm
Max hearth temperature	115 °C *
	* Constructional hearth required

General Dimensions







