

DECLARATION OF PERFORMANCE

according to Regulation (EU) 305/2011



1. Unique identification code of the product type:					
Vogue : Roomheater burning solid fuel without hot water supply					
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4) :					
Vogue (Multifuel) Midi Eco : VG-MIDM-E					
EN 13240:2001/A2:2004					
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer					
Roomheater burning solid fuel without hot water supply					
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11 (5) :					
<p>Stovax Ltd Falcon Rd Sowton Industrial Estate Exeter EX2 7LF Tel - 00 44 (0) 1392 474000 Email - info@stovax.com Web - www.stovax.com</p>					
5. Where applicable, name and contact address of authorised representative whose mandate covers the tasks specified in Article 11 (5):					
N/A					
6. System or systems of assessment and verification of consistency of performance of the construction product as set out in Annex V:					
System 3 and 4					
7. In the case of the declaration of performance concerning a construction product covered by a harmonised standard :					
The notified laboratory Kiwa - No. 0558					
performed the determination of the product type on the basis of type testing under system 3 and issued test report 60669					
8. Declared performance :					
Harmonised technical specification				EN 13240:2001/A2:2004	
Essential characteristics				Performance	
Fire safety					
Reaction to fire				A1	
Distance to combustible materials				Minimum distances, in mm	
				Side	375 mm
				Rear	375 mm
Risk of burning fuel falling out				Pass	
Emission of combustion products		CO	Wood	CO	0.11%
			Briquetted solid fuel	CO	0.04%
		Particulate emission	Wood	Pm	15 mg/m ³
			Briquetted solid fuel	Pm	15 mg/m ³
Surface temperature				Pass	
Electrical safety				Pass	
Cleanability				Pass	
Maximum operating pressure				-- bar	
Flue gas temperature at nominal heat output				T	312.0 °C
Mechanical resistance (to carry a flue / chimney)				Pass	
Thermal output					
Nominal heat output		Wood	5.00 kW	Briquetted solid fuel	5.00 kW
Room heating output		Wood	5.00 kW	Briquetted solid fuel	5.00 kW
Water heating output		Wood	-- kW	Briquetted solid fuel	-- kW
Energy efficiency		Wood η	79.5%	Briquetted solid fuel η	78.6%

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by : -

Ian Kingscott - Group Technical Director

Exeter -

03/11/2017